

HG8045H/HG8245H

GPON ONU

HUAWEI




HUAWEI

POWER PON LOS LAN1 LAN2 LAN3 LAN4 TEL1 TEL2 USB WLAN WPS

**Forward Port**

# Forward Rules >> Port Mapping Configuration



## HG8245H

Logout

[Status](#) [WAN](#) [LAN](#) [IPv6](#) [WLAN](#) [Security](#) [Route](#) **Forward Rules** [Network Application](#) [Voice](#) [System Tools](#)

**DMZ Configuration**

Port Mapping Configuration

**Port Trigger Configuration**

Forward Rules > Port Mapping Configuration

On this page, you can configure port mapping parameters to set up virtual servers on the LAN network and allow these servers to be accessed from the Internet.

Note: The well-known ports for voice services cannot be in the range of the mapping ports.

[New](#) [Delete](#)

	Mapping Name	WAN Name	Internal Host	External Host	Enable
--	--	--	--	--	--

**Mapping Name** : Port Forwarding Name

**\*External port number** : External Port

**Internal Host** : Internal IP

**Internal port number** : Internal Port (Ex. http:80, https:443, FTP:21 )

**Enable Port Mapping** : Enable

	Mapping Name	WAN Name	Internal Host	External Host	Enable
Type:	<input type="radio"/> User-defined	<input type="radio"/> Application	Web Server (HTTP) ▼		
Enable Port Mapping:	<input checked="" type="checkbox"/>				
Mapping Name:	<input type="text"/>				
WAN Name:	1_INTERNET_R_ \ ▼				
Internal Host:	<input type="text"/> * Select... ▼				
External Source IP Address:	<input type="text"/> -- <input type="text"/>				
Protocol:	TCP ▼		Internal port number:	<input type="text"/> -- <input type="text"/> *	
External port number:	<input type="text"/> -- <input type="text"/> *		External source port number:	<input type="text"/> -- <input type="text"/>	
<input type="button" value="Delete"/>					
<input type="button" value="Add"/>					
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>					

\*External port number = 1100

The screenshot shows the THDDNS management interface. On the left, there is a sidebar with the following items: "Internet No : 8800088927", "Manage Service" (highlighted in green), "Manage Account", "CPE Manual", and "Logout". The main content area is titled "Welcome aisfibre" and "Service Information". It displays the following details:

- Domain name: testing.thddns.net
- Total port: 2
- Port list table:

	Port	Note		
1	1100	<input type="text"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
2	1101	<input type="text"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

At the bottom of the service information panel, there are two buttons: "Confirm Update" and "Cancel". A red box highlights the value "1100" in the "Port" column of the first row of the "Port list" table, with a red arrow pointing to the text above it.

© 2016 THDDNS Support: support@thddns.net

Please fill in External port number to match your Port No. on THDDNS

Thank you